

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 April 2002 (18.04.2002)


PCT

(10) International Publication Number
WO 02/30550 A1

- (51) International Patent Classification⁷: **B01D 63/06, 65/00**
- (21) International Application Number: PCT/AU01/01248
- (22) International Filing Date: 3 October 2001 (03.10.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PR 0648 9 October 2000 (09.10.2000) AU
- (71) Applicant (for all designated States except US): **U.S. FILTER WASTEWATER GROUP, INC.** [US/US]; 181 Thorn Hill Road, Warrendale, PA 15086 (US).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **JOHNSON, Warren, Thomas** [AU/AU]; 125 Grose Vale Road, Grose Vale, NSW 2753 (AU). **ROGERS, Peter** [GB/GB]; Standview, 46 Morrellwood Drive, Belper, Derbyshire DE56 0JD (GB).
- (74) Agent: **BALDWIN SHELSTON WATERS**; 60 Margaret Street, Sydney, NSW 2000 (AU).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:**
— with international search report

[Continued on next page]

(54) Title: IMPROVED MEMBRANE FILTRATION SYSTEM



(57) Abstract: A method and apparatus for reducing volume of feed liquid required in a porous membrane filtration system having a number of porous membranes (6) submersed in a volume of feed liquid to be filtered, the method comprising the step of providing filler elements (9) within said volume of feed liquid to be filtered.



WO 02/30550 A1



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

TITLE: IMPROVED MEMBRANE FILTRATION SYSTEM

FIELD OF THE INVENTION

The present invention relates to membrane filtration systems, and more particularly to those systems employing porous or permeable membranes
5 located in a tank or cell open to atmosphere.

BACKGROUND ART

Any discussion of the prior art throughout the specification should in no way be considered as an admission that such prior art is widely known or forms part of common general knowledge in the field.

10 Porous membrane filtration systems require regular backwashing of the membranes to maintain filtration efficiency and flux while reducing transmembrane pressure (TMP) which rises as the membrane pores become clogged with impurities. Typically, during the backwash cycle the impurities are forced out of the membrane pores by pressurised gas, liquid or both into the
15 feed tank or cell. The liquid containing impurities and deposits from the membranes is then drained or flushed from the tank.

The waste liquid displaced from the tank needs to be disposed of or reprocessed, usually in an environmentally safe manner, so any reduction in the volume of such waste liquid is seen as advantageous in terms of environmental
20 impact and cost.

The draining or flushing of the tank, particularly when large arrays of membranes are used also requires time which results in down time of the

- 2 -

filtration cycle. In order to reduce this down time large pumping systems are required to quickly drain and refill the tank. Where tanks or cells are arranged in banks and feed is used to refill the tank, a lowering in levels in other cells may be produced during the refill process. This again impinges on operating
5 efficiency of the filtration system.

Further, in filtration systems employing gas bubble scouring of the membranes it has been found advantageous to confine the bubbles as much as possible in the region of the membranes to assist with the scouring process.

Reduction in backwash volume also reduces the volume of chemical
10 cleaning agents required in some systems. This has the two-fold advantage of reducing cost in terms of chemical requirements while also reducing waste disposal problems.

It has been found advantageous to reduce the volume of feed liquid in the filtration cell to ameliorate the above problems and provide at least some of the
15 advantages outlined above.

DISCLOSURE OF THE INVENTION

The present invention seeks to overcome one or more of the abovementioned problems of the prior art, provide one or more of the advantages outlined above or at least provide a useful alternative by reducing
20 the feed volume presented to the porous membranes in a simple, cost effective manner.

- 3 -

According to one aspect, the present invention provides a method of reducing volume of feed liquid required in a membrane filtration system having a number of porous membranes submersed in a volume of feed liquid to be filtered, the method comprising the step of providing filler elements within said
5 volume of feed liquid to be filtered.

Preferably, the filler elements substantially fill voids between the porous membranes while still permitting liquid flow communication with the membranes.

According to another aspect, the present invention provides a membrane filtration system having a number of porous membranes submersed in a volume
10 of feed liquid to be filtered, wherein one or more filler members are provided in voids between said membranes to reduce said volume.

In one preferred form the membranes are porous hollow fibre membranes arranged in bundles to form membrane modules. The modules are submersed in a liquid volume provided in a tank or cell open to atmospheric pressure. In
15 this form of the invention, the voids between the modules are at least partially filled by a filler member or members.

Preferably, the filler members are each formed of a number of elements which fit together to form an integral unit. This enables the filler members to be assembled around the membranes modules without the need for removal of the
20 modules. This assists in initial set-up as well as with replacement and maintenance regimes.

The filler elements may comprise spheres, preferably hollow, which can be packed around the membranes to fill the voids. The spheres are preferably

- 4 -

sized to avoid blocking or passing through any of the inlet/outlet ports or valves associated with the filtration system.

BRIEF DESCRIPTION OF THE DRAWINGS

Preferred embodiments of the invention will now be described, by way of
5 example only, with reference to the accompanying drawings, in which:

Figure 1 shows a perspective view of a bank of filtration modules having filler members according to one embodiment of the invention;

Figure 2 shows an enlarged perspective view of the upper portion of the bank of filtration modules of Figure 1;

10 Figure 3 shows an exploded view of the filler members of Figure 1 as they would be assembled around a filtration module;

Figure 4 shows an end elevation view of a central filler member of Figure 3;

Figure 5 shows a side elevation view of the filler member of Figure 4;

15 Figure 6 shows a perspective view of the filler member of Figure 4;

Figure 7 shows a plan view of the filler member of Figure 4;

Figure 8 shows an end elevation view of side filler member of Figure 3;

Figure 9 shows a side elevation view of the filler member of Figure 8;

Figure 10 shows a perspective view of the filler member of Figure 8;

20 Figure 11 shows a plan view of the filler member of Figure 8; and

Figure 12 shows a graph of transmembrane pressure over a period of time for two types of filtration system with a filler system being employed on one system part way through the test period.

DESCRIPTION OF PREFERRED EMBODIMENTS

- 5 -

Referring to the drawings, the embodiments will be described in relation to a manifold and filtration system disclosed in our co-pending PCT Application No. WO 00/62908 (which is incorporated herein by cross-reference), however, it will be appreciated that the invention is equally applicable to other forms of filtration
5 system requiring similar advantages.

The system includes a bank 5 of filter submodules 6 each attached in groups to a membrane filtration manifold 7. In this embodiment, the submodules 6 comprise elongate bundles of porous hollow fibre membranes (not shown) typically enclosed by a supporting cage (not shown). The
10 submodules 6 are positioned within a feed tank or cell (not shown) and when the tank is filled the sub-modules are immersed in feed liquid. Each manifold 7 is connected to a filtrate conduit 8 for removal of filtrate.

During the backwash process, the fibre bundles of submodules 6 are cleaned externally by air bubbles or a mixture of air/liquid injected into each
15 submodule to scrub the outer surfaces of the fibre membranes. The submodules 6 may also be further cleaned by backwashing liquid and/or gas through the fibre pores.

In accordance with this embodiment, in order to reduce backwash volume, each submodule 6 is encased partially by a number of filler members 9 which
20 are segmented to allow each to fit closely around the elongate fibre bundles. In this embodiment, the filler members 9 are spaced from the upper and lower manifolds 7 to allow for flow of liquid and/or impurities in and out of the submodules 6. It will be appreciated that other arrangements to allow liquid flow can also be employed, for example, the filler members 9 could be spaced
25 radially from the outer periphery of each fibre bundle submodule 6 or various

- 6 -

shapes of filler member 9 could be used which allowed for liquid flow to and from the submodule 6 while still substantially filling the voids between each submodule 6.

In this system, which employs a gas bubble scouring method, the use of the filler members 9 provides an additional advantage of confining the gas bubbles within the submodules 6 and thus improving scouring efficiency.

As best shown in Figures 3 to 11, the filler members 9 are formed from complementary segments comprising a central or core element 10 having two sets of parallel opposed semi-circular, in cross-section, channels 11 extending longitudinally along the length of the central element 10. The channels 11 have a diameter sized to accommodate and fit closely around the submodule 6. The sides 12 and inner edge 13 of the element 10 are provided with outwardly extending tabs or bosses 14 which mate with complementary slots 15 on other filler segments 16 to provide, in use, an integral filler member 9.

The side filler segments 16 are generally T-shaped in cross-section with half-semi circular sides 17 of the same diameter as the central element 10.

The top and bottom surface 18 of the central element 10 are provided with a spacer peg 19 which positions the filler element 9 in a spatial relationship from the manifold 7 to allow fluid flow to and from the top and bottom of the fibre bundles.

The filler members 9 are desirably formed from material which is resistant to any destructive substances present in the feed stream as well as chemicals, gases, etc. which may be used in the backwash or other cleaning processes.

The filler members 9 are also desirably of neutral buoyancy so they will remain in position during submersion of the submodules in the feed tank. They can be

- 7 -

formed from foamed plastics material such as polyethylene foam or blow or rotor moulded plastic. When blow-moulded, the filler elements may be hollow to allow for filling with a fluid (usually water) to produce the required neutral buoyancy.

5 Figure 12 shows the effect on the transmembrane pressure characteristics of two filtration machines. The upper graph shows a machine without the filler members whereas the lower graph shows a machine with filler members employed part way through the test cycle. This graph demonstrates the improved effectiveness of the backwash when filler members are employed.

10 It will be appreciated that further embodiments and exemplifications of the invention are possible without departing from the spirit or scope of the invention described.

- 8 -

CLAIMS:

1. A method of reducing volume of feed liquid required in a porous membrane filtration system having a number of porous membranes submersed in a volume of feed liquid to be filtered, the method comprising the step of
5 providing filler elements within said volume of feed liquid to be filtered.
2. A method according to claim 1 wherein the filler elements substantially fill voids between the porous membranes while still permitting liquid flow communication with the membranes.
3. A membrane filtration system having a number of porous membranes
10 submersed in a volume of feed liquid to be filtered, wherein one or more filler members are provided in voids between said membranes to reduce said volume.
4. A membrane filtration system according to claim 3 wherein the membranes are porous hollow fibre membranes arranged in bundles to form membrane
15 modules.
5. A membrane filtration system according to claim 4 wherein the modules are submersed in a liquid volume provided in a tank or cell open to atmospheric pressure.
6. A membrane filtration system according to claim 4 or 5 wherein the voids
20 between the modules are at least partially filled by the filler member or members.

- 9 -

7. A membrane filtration system according to claim 3 wherein the filler members are each formed of a number of elements which fit together to form an integral unit.
8. A membrane filtration system according to claim 3 wherein said filler
5 members are neutrally buoyant with respect to said feed liquid.
9. A membrane filtration system according to claim 3 wherein said filler members are spherical in shape.
10. A membrane filtration system according to claim 8 or claim 9 wherein said filler elements are hollow and adapted to be filled with a fluid to provide said
10 neutral buoyancy.
11. A membrane filtration system according to claim 4 wherein the filler member is formed from complementary segments comprising a central element having two sets of parallel opposed semi-circular, in cross-section, channels extending longitudinally along the length of the central element, each channel
15 have a diameter sized to accommodate and fit closely around the fibre bundles, and side filler segments of generally T-shaped cross-section with half-semi circular sides of the same diameter as said channels adapted to engage with said central element to form said filler member.
12. A membrane filtration system according to claim 11 wherein each filler
20 member includes complementary engagement formations for engaging with associated engagement means on other filler members.
13. A membrane filtration system according to claim 3 wherein the filler member is formed of foamed plastics material.

- 10 -

14. A membrane filtration system according to claim 3 wherein the filler member is formed of blow-moulded plastics material.

15. A membrane filtration system according to claim 3 wherein the filler member is formed of rotor-moulded plastics material.











FIG. 1










FIG.12

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU01/01248

A. CLASSIFICATION OF SUBJECT MATTERInt. Cl. ⁷: B01D 63/06, 65/00

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

B01D 63/06, 65/00

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

AU:IPC AS ABOVE

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

WPAT: SPACER, FILLER, SEPARATOR, MODUL, DIVID

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	Derwent Abstract Accession No.96-054187/06, Class J01 JP07313851 A (KUBOTA CORP) 5 December 1995	
A	WO 00/09245 A (MITSUBISHI RAYON CO. LTD) 24 February 2000	
A	Derwent Abstract Accession No.98-431717/37, ClassD15 J01 JP 10180053 A (NITTO DENKO CORP) 7 July 1998	

☐

Further documents are listed in the continuation of Box C

☐

See patent family annex

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier application or patent but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T"

later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X"

document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y"

document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&"

document member of the same patent family

Date of the actual completion of the international search

21 November 2001

Date of mailing of the international search report

23 NOV 2001

Name and mailing address of the ISA/AU

AUSTRALIAN PATENT OFFICE
 PO BOX 200, WODEN ACT 2606, AUSTRALIA
 E-mail address: pct@ipaustalia.gov.au
 Facsimile No. (02) 6285 3929

Authorized officer

ASOKA DIAS-ABEYGUNAWARDENA

Telephone No : (02) 6283 2141